


LDL252

5w LED Downlight with LLR17 module



General Information

Housing Material:	Aluminium	Diffuser Material:	N/A
Colour (RAL):	White(9016) - Black(9004)	Weight:	108g (Lamp)
Dimensions (L-W-H):	Dia.81mm – H86mm	Cut hole :	68mm
Connection:	AC Connector	Installation:	Recessed Mounted
Rotation Angle:	N/A	Tilting Angle:	N/A
Temperature:	-20 ~ +35°C	Accessories:	N/A

Photometrical Data

LED Manufacturer:	Luminus	LED Type:	CXM-6
CCT:	2700K - 3000K - 4000K	CRI(Minimum):	90
lm system (±5%):	497lm - 516lm - 541lm	lm Module:	585lm - 607lm - 637lm
Luminous Efficiency:	76lm/w - 79lm/w - 83lm/w	MacAdam:	3
Optic:	Reflector + Anti-Dazzle Cover	Beam Angle:	22°/43°/55°
UGR:	<19	LifeSpan (Ta25°C):	>50.000h - L70B50

Electrical Data

Driver:	TRIDONIC	Input Voltage:	220-240VAC 50/60Hz
Output Voltage:	33-47VDC	Output Current:	150mA
Displacement Factor:	>0.5	Current Ripple:	±5%
W system:	6.5W	Ballast Losses:	1.3W
Control:	ON/OFF	Minimum Dimming:	N/A
Inrush Current:	10A / 115µs	Max No. of Units	B10/13/16 = 55/69/83
		per MCB:	C10/13/16 = 92/115/138

LDL252

5w LED Downlight with LLR17 module



Accessories

			
AS	BK	CH	RB